

NOMAN SERIES**AUTOMATIC GUIDED TRACTORS****DRC230-A DRC530-A**


AUTOMATIC GUIDED TRACTORS
DRC230-A DRC530-A
Towing Capacity 500kg 1,000kg

- Automatic transport is realized easily in small budget.
- Mass transport is available by tractor and trailers.
- Easy operation and superior safety.
- Various automatic travel is available by options.

**KOLEC Co.,Ltd.**

NOMAN SERIES DRC230-A DRC530-A

Towing Capacity 500kg 1,000kg



Feature

Automatic transport is realized easily in small budget.

DRC tractors realize automatic transport easily. Furthermore, the budget is small. We support your low cost operation of transfer.

Mass transport available.

Automatic guided tractors make mass carrying, because it tows plural trailers.

Easy operation and superior safety

You can order the operation which is starting and stopping easily by onboard operator panel. Our tractor has a lay of features for safety. Tractor informs somebody of automatic driving by flashing light and warning sound. If the tractor gets contact with an obstacle, the contact bumper merge the shock and it stop emergency.

Good response for various automatic travel.

We offer some options which are short cutting to the destination and diverge from main travel route for quick transport.

Technical Data

| Technical Data | | DRC230-A | DRC530-A |
|--------------------------|----------------|--|-----------------|
| Towing capacity | kg | 500 | 1,000 |
| Travelling speed | Loaded m/min | 36 | 33 |
| | unloaded m/min | 40 | 40 |
| Wheel base | mm | 500 | 680 |
| Minimum turning radius | mm | 1,500 | 1,500 |
| Service weight | kg | 200 | 300 |
| Drive motor | | 1 X 250w | 1 x 400w |
| Battery | 5HR | 2 X 12V / 50Ah | 2 X 12V / 100Ah |
| Induction type | | Electromagnetic guidance / * magnetic guidance | |
| Travel direction | | Forward travel | |
| Destination setting | | 5 Stations | |
| Control | | Onboard operator panel | |
| Dimensions | | | |
| Overall length | mm | 1,200 | 1,380 |
| Overall width | mm | 650 | 650 |
| Height of body | mm | 580 | 580 |
| Height of flashing light | mm | 710 | 710 |
| Minimum ground clearance | mm | 50 | 50 |

* option

Options

1. Station selector
2. Diverge and merge
3. Guidance by ground side device

NORMAN SERIES AGV



TRT 330/530

TRT 230

KOLEC Co.,Ltd.

3-3-5 Tenmabashi, Kita-ku, Osaka, Japan

Home page <http://www.kolec.co.jp/>